

Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

Product identifier:

Product name: Ethanol(99.5)

Product code (SDS NO): 17065jis_E1-4

Details of the supplier of the safety data sheet

Manufacturer/Supplier: JUNSEI CHEMICAL CO., LTD.

Address: 1-6, Ohmano-cho, Koshigaya-shi, Saitama 343-0844, Japan

Division: Quality Assurance Department

Telephone number: +81-48-986-6161

FAX: +81-48-989-2787

e-mail address: shiyaku-t@junsei.co.jp

2. Hazards identification

GHS classification and label elements of the product

Classification of the substance or mixture

PHYSICAL AND CHEMICAL HAZARDS

Flammable liquids: Category 2

HEALTH HAZARDS

Serious eye damage/eye irritation: Category 2B

Carcinogenicity: Category 1A

Reproductive toxicity: Category 1A

Specific target organ toxicity – single exposure: Category 3 (Respiratory tract irritation)

Specific target organ toxicity – single exposure: Category 3(Narcosis)

Specific target organ toxicity – repeated exposure: Category 1(liver)

Specific target organ toxicity – repeated exposure: Category 2(central nervous system)

(Note) GHS classification without description: Not classified/Classification not possible

Label elements



Signal word: Danger

HAZARD STATEMENT

H225-Highly flammable liquid and vapor

H320-Causes eye irritation

H350-May cause cancer

H360-May damage fertility or the unborn child

H335-May cause respiratory irritation

H336-May cause drowsiness or dizziness

H372-Causes damage to organs through prolonged or repeated exposure

H373-May cause damage to organs through prolonged or repeated exposure

PRECAUTIONARY STATEMENT

Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Ethanol(99.5),JUNSEI CHEMICAL CO., LTD.,17065jis_E1-4,22/04/2020

- Use explosion-proof electrical/ventilating/lighting equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Do not breathe dust/fume/gas/mist/vapors/spray.
- Use only outdoors or in a well-ventilated area.
- Wash contaminated parts thoroughly after handling.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Use personal protective equipment as required.
- Do not eat, drink or smoke when using this product.

Response

- In case of fire: Use appropriate media extinction.
- Get medical advice/attention if you feel unwell.
- IF exposed or concerned: Get medical advice/attention.
- Call a POISON CENTER or doctor/physician if you feel unwell.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.

Storage

- Store in a well-ventilated place. Keep container tightly closed. Keep cool.
- Store locked up.

Disposal

- Dispose of contents/container in accordance with local/national regulation.

Specific Physical and Chemical hazards

- Highly flammable liquid. Vapor/air mixture may explode.

3. Composition/information on ingredients

Mixture/Substance selection:

Substance

Common name, synonyms: Ethyl alcohol (99.5)

Ingredient name:Ethanol
Content (%):99.5
Chemical formula:C2H5OH
Chemicals No, Japan:2-202
CAS No.:64-17-5
MW:46.07
ECNO:200-578-6

4. First-aid measures

Descriptions of first-aid measures

General measures

- Get medical attention/advice if you feel unwell.

IF INHALED

- Remove person to fresh air and keep comfortable for breathing.
- Call a POISON CENTER or doctor/physician if you feel unwell.

IF ON SKIN (or hair)

- Take off immediately all contaminated clothing. Rinse skin with water/shower.
- If skin irritation or rash occurs: Get medical advice/attention.

IF IN EYES

- Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF SWALLOWED

Rinse mouth.

Call a POISON CENTER or doctor/physician if you feel unwell.

Most important symptoms and effects, both acute and delayed

(Symptoms when inhalation or ingestion)

Cough. Headache. Fatigue. Drowsiness. Burning sensation. Headache. Confusion. Dizziness.

Unconsciousness.

(Symptoms when skin and/or eye contact)

Dry skin. Redness of the eyes. Pain of the eyes. Burning sensation of the eyes.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

In case of fire, use water mist, alcohol-resistant foam, dry powder, CO2 to extinguish.

Unsuitable extinguishing media

Do not use direct water jet.

Specific hazards arising from the substance or mixture

Containers may explode when heated.

Fire may produce irritating, corrosive and/or toxic gases.

Runoff from fire control or dilution water may cause pollution.

Advice for firefighters

Specific fire-fighting measures

Evacuate non-essential personnel to safe area.

Cool container with water spray.

Special protective equipment and precautions for fire-fighters

Wear fire/flame resistant/retardant clothing.

Wear protective gloves/protective clothing/eye protection/face protection.

Firefighters should wear self-contained breathing apparatus with full face piece operated positive pressure mode.

6. Accidental release measures

Personnel precautions, protective equipment and emergency procedures

Keep unauthorized personnel away.

In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.

Ventilate area until material pick up is complete.

Wear proper protective equipment.

PUBLIC SAFETY: Ventilate closed spaces before entering.

Environmental precautions

Runoff to sewer may create fire or explosion hazard.

Vapor explosion hazard indoors, outdoors or in sewers.

Avoid release to headsprings, rivers, lakes, ocean and groundwater.

Methods and materials for containment and cleaning up

Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Use clean non-sparking tools to collect absorbed material.

All equipment used when handling the product must be grounded.

Preventive measures for secondary accident

Collect spillage.

Stop leak if you can do it without risk.

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Prevent entry into waterways, sewers, basements or confined areas.

7. Handling and storage

Precautions for safe handling

Preventive measures

(Exposure Control for handling personnel)

Do not breathe dust/fume/gas/mist/vapors/spray.

(Protective measures against fire and explosion)

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

(Exhaust/ventilator)

Exhaust/ventilator should be available.

(Safety treatments)

Avoid contact with skin.

Avoid contact with eyes.

Safety Measures

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

When using do not eat, drink or smoke.

Any incompatibilities

Strong oxidizing agents, Calcium hypochlorite, Silver oxide, Ammonia should not be mixed with the chemicals.

Advice on general occupational hygiene

Wash contaminated parts thoroughly after handling.

Do not eat, drink or smoke when using this product.

Storage

Conditions for safe storage

Store in a well-ventilated place. Keep container tightly closed.

Keep cool. Protect from sunlight.

Store locked up.

8. Exposure controls/personal protection

Control parameters

Control value in MHLW is not available.

Adopted value

Adopted value in JSOH is not available.

ACGIH(2008) STEL: 1000ppm (URT irr)

OSHA-PEL

TWA: 1000ppm, 1900mg/m³

NIOSH-REL

TWA: 1000ppm

Exposure controls

Appropriate engineering controls

Do not use in areas without adequate ventilation.

Eye wash station should be available.

Washing facilities should be available.

Individual protection measures**Respiratory protection**

Wear respiratory protection.

Wear positive pressure self-contained breathing apparatus (SCBA).

Hand protection

Wear protective gloves. Recommended material(s): butyl rubber, viton

Consult with your glove and/or personnel equipment manufacturer for selection of appropriate compatible materials.

Eye protection

Wear safety glasses with side-shields.

Wear eye/face protection.

Skin and body protection

Wear impervious clothing and boots in case of repeated or prolonged treatment.

9. Physical and Chemical Properties**Information on basic physical and chemical properties**

Physical state: Volatile liquid

Color: Colorless

Odor: Characteristic odor

Odor threshold: 10ppm

pH: 7.0(10g/L, 20°C)

Boiling point or initial boiling point: 78°C

Boiling range data is not available.

Melting point/Freezing point: -114°C

Decomposition temperature: >=700°C

Self-Accelerating Decomposition Temperature/SADT data is not available.

Flammability (gases, liquids and solids): Ignitable

Flash point: (C.C.) 12.0°C

Auto-ignition temperature: 400°C

Critical temperature: 243.1°C

Lower and upper explosion limit/flammability limit:

Lower explosion limit: 3.1 vol %

Upper explosion limit: 27.7 vol %

Vapor pressure: 5.8 kPa (20°C)

VOC data is not available.

Relative vapor density (Air=1): 1.6

Relative density of the Vapor/air - mixture at 20°C (Air = 1): 1.03

Density and/or relative density: 0.789~0.791g/ml (20°C)

Dynamic viscosity: 1.074mPas(20°C)

Kinematic viscosity data is not available.

Solubility:

Solubility in water: Miscible

Solubility in solvent: Very soluble in diethyl ether.

n-Octanol/water partition coefficient: log Pow-0.32

10. Stability and Reactivity**Reactivity**

Runaway polymerization will not occur.

Chemical stability

Stable under normal storage/handling conditions.

Highly flammable.

Possibility of hazardous reactions

The vapour mixes well with air, explosive mixtures are easily formed.

Reacts slowly with calcium hypochlorite, silver oxide and ammonia. This generates fire and explosion hazard.

Reacts violently with strong oxidants such as nitric acid, silver nitrate, mercuric nitrate and magnesium perchlorate. This generates fire and explosion hazard.

Conditions to avoid

Contact with incompatible materials.

Open flames. Heat. Sparks.

Incompatible materials

Strong oxidizing agents, Calcium hypochlorite, Silver oxide, Ammonia

Hazardous decomposition products

Carbon oxides

11. Toxicological Information**Information on toxicological effects****Acute toxicity****Acute toxicity (Oral)**

[GHS Cat. Japan, base data]

rat LD50=6200~13700mg/kg (PATTY 6th, 2012)

Acute toxicity (Dermal)

[GHS Cat. Japan, base data]

rabbit LDLo= 20000 mg/kg (SIDS, 2005)

Acute toxicity (Inhalation)

[GHS Cat. Japan, base data]

vapor : rat LC50=63000 ppmV (DFGOT vol.12, 1999)

Irritant properties**Skin corrosion/irritation**

[GHS Cat. Japan, base data]

rabbit (OECD TG404) : not irritating (SIDS, 2005)

Serious eye damage/irritation

[GHS Cat. Japan, base data]

rabbit : moderate eye irritation (⊗:recover within 7 days) (ECETOC TR No.48(2), 1998 et al.)

Allergenic and sensitizing effects data is not available.

Mutagenic effects data is not available.

Carcinogenicity

[GHS Cat. Japan, base data]

cat.1A; (ACGIH 7th, 2012; IARC, 2010)

IARC-Gr.1 : Carcinogenic to humans

ACGIH-A3(2008) : Confirmed Animal Carcinogen with Unknown Relevance to Humans

Reproductive toxicity

[GHS Cat. Japan, base data]

cat. 1A; human : PATTY 6th, 2012

Teratogenic effects

human : Fetal alcohol syndrome is growth, mental, and physical problems that may occur in a baby when a mother drinks alcohol during pregnancy.

STOT**STOT-single exposure**

[cat.3 (resp. irrit.)]

[GHS Cat. Japan, base data]

respiratory tract irritation (PATTY 6th, 2012)

[cat.3 (drow./dizz.)]

[GHS Cat. Japan, base data]

narcosis (PATTY 6th, 2012; SIDS, 2005)

STOT-repeated exposure

[cat.1]

[GHS Cat. Japan, base data]

liver (DFGOT vol.12, 1999)

[cat.2]

[GHS Cat. Japan, base data]

CNS (HSDB, Access on Jun. 2013)

Aspiration hazard data is not available.

12. Ecological Information

Ecotoxicity

Aquatic toxicity

Hazardous to the aquatic environment (Acute)

[GHS Cat. Japan, base data]

Algae (Chlorella) EC50=1000mg/L/96hr (SIDS, 2005)

Hazardous to the aquatic environment (Long-term)

[GHS Cat. Japan, base data]

Crustacea (Ceriodaphnia reticulata) NOEC=9.6mg/L/10days (SIDS, 2005)

Water solubility

miscible (ICSC, 2018)

Persistence and degradability

Degrade rapidly [BOD_Degradation : 89% (Registered chemicals data check & review, 1993)]

Bioaccumulative potential

log Pow=-0.32 (ICSC, 2018)

Mobility in soil

Mobility in soil data is not available.

Other adverse effects

Ozone depleting chemical data is not available.

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging

Waste treatment methods

Dispose of contents/container in accordance with local/national regulation.

14. Transport Information

UN No., UN CLASS

UN No.: 1170

Proper Shipping Name :

ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

Class or division : 3

Packing group : II

ERG GUIDE No.: 127

IMDG Code (International Maritime Dangerous Goods Regulations)

UN No.: 1170

Proper Shipping Name :

ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

Class or division : 3

Ethanol(99.5),JUNSEI CHEMICAL CO., LTD.,17065jis_E1-4,22/04/2020

Packing group : II

IATA Dangerous Goods Regulations

UN No.: 1170

Proper Shipping Name :

ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

Class or division : 3

Hazard labels : Flamm.liquid

Packing group : II

Environmental hazards

MARPOL Annex III – Prevention of pollution by harmful substances

Marine pollutants (yes/no) : no

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Environmental hazards

MARPOL Annex V – Prevention of pollution by garbage discharge

Carcinogenicity: cat.1, 1A, 1B

Ethanol

Reproductive toxicity: cat.1, 1A, 1B

Ethanol

Specific target organ toxicity – repeated exposure: cat.1

Ethanol

Transport in bulk according to Annex II of MARPOL73/78 and IBC Code

Noxious Liquid ; Cat. Z

Ethanol

Basel law, Japan

Ethanol

US Federal Regulations

Chemicals listed in TSCA Inventory

Ethanol

Other regulatory information

We are not able to check up the regulatory information with regard to the substances in your country or region, therefore, we request this matter would be filled by your responsibility.

Regulatory information with regard to this substance in your country or in your region should be examined by your own responsibility.

Ensure this material in compliance with federal requirements and ensure conformity to local regulations.

Regulatory information in this section are limited to intentional ingredient(s), but does not contain information on non-intentional ingredients or impurities which are not informed by supplier(s).

16. Other information

GHS classification and labelling

H225–Flam. Liq. 2: H225 Highly flammable liquid and vapor

H320–Eye Irrit. 2B: H320 Causes eye irritation

H350–Carc. 1A: H350 May cause cancer

H360–Repr. 1A: H360 May damage fertility or the unborn child

H335–STOT SE 3: H335 May cause respiratory irritation

H336–STOT SE 3: H336 May cause drowsiness or dizziness

H372–STOT RE 1: H372 Causes damage to organs through prolonged or repeated exposure

H373–STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure

Reference Book

Globally Harmonized System of classification and labelling of chemicals, (6th ed., 2015), UN Recommendations on the TRANSPORT OF DANGEROUS GOODS 20th edit., 2017 UN IMDG Code, 2018 Edition (Incorporating Amendment 39-18)
IATA Dangerous Goods Regulations (61th Edition) 2020
Classification, labelling and packaging of substances and mixtures (Table 3 ECNO6182012)
2016 EMERGENCY RESPONSE GUIDEBOOK (US DOT)
2019 TLVs and BEIs. (ACGIH)
<http://monographs.iarc.fr/ENG/Classification/index.php>
JIS Z 7253 : 2019
JIS Z 7252 : 2019
2019 Recommendation on TLVs (JSOH)
Supplier's data/information
Chemicals safety data management system "GHS Assistant" (<https://www.asahi-ghs.com/>)
NITE Chemical Risk Information Platform (NITE-CHRIP)
https://www.nite.go.jp/en/chem/chrip/chrip_search/systemTop
GHS Classification Guidance for Enterprises 2013 Revised Edition (Aug. 2013, METI)

General Disclaimer

This data sheet was created based on the information we currently have and may be revised according to new information. In addition, the precautions apply only to normal handling, and in the case of special handling, please make adequate countermeasure to maintain your safety.

The data given here is based on current knowledge and experience. The purpose of this Safety Data Sheet is to describe the products in terms of their safety requirements. The data does not signify any warranty with regard to the products' properties.

The GHS classification data given here is based on current Japan official data (NITE published in 2018).